

DISSOLVED OXYGEN (DO) with ATC ECONOMY PORTABLE METER



SM 600

Dissolved Oxygen (DO) portable meter Polarographic probe

Smart meters are manufactured to be easy to use, practical and accurate. Ideal for the classroom, laboratory or for general field use.

Affordable Dissolved Oxygen meter comes with Dissolved Oxygen probe and 2 spare membranes. Manual 1 or 2 point (zero and slope) calibration with a Range of 0.0 to 19.9 mg/L or ppm dissolved oxygen per Liter.

The instrument can be calibrated using the trimmer provided on the back. This model is supplied complete with a professional electrode/probe, calibration solution, a 9V battery, instruction manual and screwdriver for calibration.

Dissolved Oxygen

Item	Range	Accuracy	ATC	Calibration	Electrode
SM600	0.0 – 19.9 ppm	± 1.5% full scale	-	Manual 1 or 2 points	MA840



DISSOLVED OXYGEN (DO) ECONOMY PORTABLE METER

SM600

Specifications:

Range	0.0 - 19.9 ppm
Resolution	0.1 ppm
Accuracy	± 1.5% full scale
Calibration	Manual 1 or 2 points
Temp. Compensation	Automatic from 0 - 30°C
Battery type/life	1 x 9V / 300 hours
Environment	0 – 50°C/95% RH Max
Dimensions	80 x 145 x 35 mm



SM 600

Simple to use and low costs Dissolved Oxygen meter

- Manual 1 or 2 point calibration
- Low battery indicator
- Automatic Temperature Compensation

